

1000/32 REVERSE VENTED: S220 - 0.7mm

©Thomas Panels & Profiles Limited. 15/01/25 - Daniel Dowse Technical Sales

DEFLECTION LIMIT L/150 FOR BOTH POSITIVE AND NEGATIVE LOADING

Limiting Values (kN/m²)	Gravity	Span (m)	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6
		Single	2.57	2.12	1.79	1.52	1.31	1.14	1.00	0.89	0.79	0.71	0.64	0.58	0.53	0.49	0.43	0.38	0.34
		Double	3.65	3.13	2.71	2.38	2.10	1.87	1.68	1.51	1.37	1.25	1.14	1.05	0.94	0.82	0.72	0.64	0.57
		Multi	4.39	3.77	3.28	2.88	2.54	2.27	2.03	1.84	1.67	1.46	1.25	1.08	0.94	0.82	0.72	0.64	0.57
	Uplift	Span (m)	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6
		Single	4.85	4.01	3.37	2.87	2.47	2.15	1.89	1.64	1.38	1.17	1.01	0.87	0.76	0.66	0.58	0.52	0.46
		Double	2.38	2.01	1.73	1.50	1.31	1.14	1.00	0.89	0.79	0.71	0.64	0.58	0.53	0.49	0.45	0.41	0.38
		Multi	2.90	2.46	2.11	1.83	1.61	1.42	1.26	1.11	0.99	0.89	0.80	0.73	0.66	0.61	0.56	0.51	0.48

These tables have been produced by SCI on behalf of Thomas Panels and Profiles in accordance with BS EN 1993-1-3:2006. The loads presented in the tables below represent the total characteristic load that can be applied to the profile for a given span. In design, this value must include the self-weight of the profile along with any other permanent or imposed loads.

1000/32 REVERSE VENTED: LOAD SPAN TABLE

1000/32 REVERSE VENTED: S220 - 0.5mm

©Thomas Panels & Profiles Limited. 15/01/25 - Daniel Dowse Technical Sales

DEFLECTION LIMIT L/150 FOR BOTH POSITIVE AND NEGATIVE LOADING

Limiting Values (kN/m²)	Gravity	Span (m)	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6
		Single	1.49	1.23	1.04	0.88	0.76	0.66	0.58	0.52	0.46	0.41	0.37	0.34	0.31	0.28	0.26	0.23	0.21
		Double	1.73	1.49	1.30	1.14	1.01	0.90	0.81	0.73	0.66	0.61	0.56	0.51	0.47	0.44	0.40	0.38	0.34
		Multi	2.07	1.79	1.56	1.37	1.22	1.09	0.98	0.89	0.81	0.74	0.68	0.62	0.57	0.50	0.44	0.39	0.34
	Uplift	Span (m)	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6
		Single	2.45	2.05	1.73	1.47	1.27	1.10	0.97	0.86	0.77	0.67	0.57	0.50	0.43	0.38	0.33	0.29	0.26
		Double	1.26	1.07	0.93	0.81	0.71	0.63	0.56	0.50	0.45	0.41	0.37	0.34	0.31	0.28	0.26	0.24	0.22
		Multi	1.53	1.30	1.13	0.98	0.86	0.77	0.69	0.62	0.56	0.51	0.46	0.42	0.39	0.35	0.32	0.30	0.28

These tables have been produced by SCI on behalf of Thomas Panels and Profiles in accordance with BS EN 1993-1-3:2006. The loads presented in the tables below represent the total characteristic load that can be applied to the profile for a given span. In design, this value must include the self-weight of the profile along with any other permanent or imposed loads.

1000/32 REVERSE VENTED: LOAD SPAN TABLE